

## Product Data Sheet

# Knauf Schnellgrund



**Knauf Schnellgrund is a ready-mixed flooring primer, for use on all Knauf flooring panels in preparation for flooring finishes to be applied. Also can be used on a substrate prior to attaching pedestals.**

### Areas of Application

Directly onto Knauf Flooring panels prior to flooring finishes being applied, or flooring substrate before pedestals are attached.

### Compliance Standards

This product does not have a harmonised standard to allow for CE marking and or designated standard to allow for UKCA marking.

### Key Benefits

- Quick drying
- Ready to use
- Yellow colour for ease of application
- Primer and dust proofer prior to pedestal adhesion
- Suitable for use with all Knauf flooring panels
- Improved bonding properties as a primer prior to the application of floor fillers, floor finishes (e.g. tiles), gypsum fibre floor panels
- Rated EMICODE® EC1 plus for very low emissions

### Technical information

Colour	Weight (kg)	Approximate Coverage (m <sup>2</sup> per 5kg tub)	Material Number
Yellow	5	80	448267

## Sustainability

### Substances of very high Concern (SVHC)

At the time of publication, under REACH UK and REACH EU regulations this product contains no SVHC. For more information please consult the Safety Data Sheet.

### Volatile Organic Compound Content (VOC)

< 0.1% (max. 1g/l).

## Storage and Handling

Store in a cool environment between 5°C to 25°C. Close the opened tub after use to keep airtight. Do not expose to direct sunlight or heat.

## Packaging

In a recycled plastic tub, recyclable after use.

## Shelf Life

18 months in the sealed tub.

## Disposal

Disposal should be in accordance with local authority requirements. European waste codes: 08 01 20 - aqueous suspensions containing paint or varnish other than those mentioned in 08 01 19. Containers should be cleaned before recycling to minimise contamination.

## Health & Safety

Avoid contact with skin and eyes. Do not breathe gas/fumes/vapour/spray. Wear gloves, and safety goggles with side shields when splashing is a risk. Refer to the safety data sheet for more information.

## Application / Installation

Ensure the substrate is free from dust, debris and grease as well as dimensionally stable. Stir the contents of the tub, apply undiluted crosswise using a painters brush, prime brush or roller ensuring a uniform and fully covering application. Remove any excess build up to avoid glossy spots. Clean tools immediately after use with water. Ventilate rooms and wait until Schnellgrund is fully dried (at least 2 hours at 20°C and 65% RH). Schnellgrund remains slightly sticky even after completely drying.

## Additional Documentation

[Safety Data Sheet](#)



### Customer Service

UK Tel: 0800 521 050  
Eire Tel: 01 4620739  
Email: [cservice@knauf.com](mailto:cservice@knauf.com)

### Technical Service

0800 521050 (option 2)  
Live Webchat 09:00 -17:00  
[technical-uk@knauf.com](mailto:technical-uk@knauf.com)

### Website

[www.knauf.co.uk](http://www.knauf.co.uk)  
[www.knauf.ie](http://www.knauf.ie)

### Address (UK)

Knauf  
Kemsley Fields Business Park  
Sittingbourne  
Kent ME9 8SR

### Address (Ireland)

Knauf  
87 Broomhill Road  
Tallaght  
Dublin 24  
D24 WR85

The information given in this publication is believed to be current and accurate as at the date of publication, but no warranty, express or implied is given. Updates will not be automatically issued.  
© Copyright Knauf 2024

Creation Date: 03/07/2024  
Revision Reference: 001  
Revision Date: 03/07/2024