

Product Data Sheet

Knauf Fibreglass Tape



Knauf Fibreglass tape provides strong joints which avoid cracking and have a flawless, flat surface when used with Knauf ready-mixed and powdered jointing compounds.

Areas of Application

Plasterboard walls and ceilings.

Compliance Standards

This product does not conform to any harmonised standards and is therefore not CE/UKCA marked.

Key Benefits

- Lower absorption of water from the jointing compound leading to less shrinkage
- Ideal for refurbishments
- For strong joints which avoid cracking

Technical information

Dimensions & Weights				
Width (mm)	Length (m)	Colour	Weight (kg)	Material Number
50	25	White	0.05	3698

Sustainability

Substances of very high Concern (SVHC)

At the time of publication, under REACH UK and REACH EU regulations this product contains no SVHC. For more information please consult the Safety Data Sheet.

Storage and Handling

No specific education is required for safe handling. Avoid damp conditions for storage.

Packaging

Packaged in an outer cardboard box.

Disposal/Repair

Any excess leftover product can be saved for another project or recycled in accordance with local authority requirements. Fibreglass Joint Tape which has joint compound on should be disposed of according to the requirements of the joint compound.

Health & Safety

No special precautions are necessary but the use of gloves are recommended during the handling and installation of this product.

Application / Installation

To use to complete tape and jointing finishes to tapered edge plasterboard: Use a minimum of 1mm of Knauf jointing compound (joint filler premium/joint cement premium or fill & finish) to bed the tape and fill to the shoulder of the taper of the plasterboard. Add a liberal coat of Knauf Joint Filler Premium over the top, fill the joint to the shoulder of the taper. Smooth and allow to set. Once set, apply Knauf Joint Cement Premium or Fill & Finish Light over the entire layer to approximately 50mm extra either side of the first coat and leave to dry. Repeat, and when fully dry, sand if needed. Jointing should be completed in accordance with BS 8000-8:2023.



Customer Service

UK Tel: 0800 521 050
Eire Tel: 01 4620739
Email: cservice@knauf.com

Technical Service

0800 521050 (option 2)
Live Webchat 09:00 -17:00
technical-uk@knauf.com

Website

www.knauf.co.uk
www.knauf.ie

Address (UK)

Knauf
Kemsley Fields Business Park
Sittingbourne
Kent ME9 8SR

Address (Ireland)

Knauf
87 Broomhill Road
Tallaght
Dublin 24
D24 WR85

The information given in this publication is believed to be current and accurate as at the date of publication, but no warranty, express or implied is given. Updates will not be automatically issued.

© Copyright Knauf 2024

Creation Date: 17/05/2024
Revision Reference: 001
Revision Date: 17/05/2024